

MT5 Quick-Release Mount

User Manual

Description

Our MT5 quick-release mount is meticulously engineered for the seamless installation of digital and thermal imaging riflescopes onto your dependable hunting shotgun. Crafted from corrosion-resistant materials, its durability ensures a lifetime of dependable performance. Additionally, it offers customization options for scope height and eye relief, enhancing the ergonomic fit with your rifle.


While initially intended for compatibility with PARD DS 3x Series, TS 3x Series, and TD Series scopes, it also readily accommodates any other 30mm scope of your choosing. This adaptability makes it a versatile choice for various firearm setups.

Key features

- Effortless Installation: Mount your digital or thermal imaging riflescopes on your hunting shotgun in seconds, no tools required!
- Fully compatible with all 30mm diameter tube scopes.
- Swift Transitions: Switch between different optics and setups with ease, thanks to the quick-release mechanism.
- An essential accessory for PARD DS 3x Series, TS 3x Series and TD Series riflescopes.
- Rugged Durability: Crafted for the rigors of the hunt, the MT5 is built to withstand the toughest conditions.

Upgrade your hunting game with the PARD MT5 Quick-Release Mount – where convenience meets reliability!

Dimensions (mm)



Note: Use M6 screws to fix the mount on the riflescopes.

Installation

Step 1: Attachment to Riflelescope


Using M6 screws, securely attach the MT5 mount to your riflelescope. Be sure to fasten them appropriately.

Step 2: Assembly on the Picatinny Rail

Place your riflelescope in a comfortable position on the Picatinny rail.

Step 3: Initial Setup (First Use)

For your initial use, it's essential to tighten the fastening screws as shown in the following picture. Adjust them according to the size of your Picatinny rail.




Step 4: Secure Fastening Screws

Once the fastening screws are appropriately tightened, secure them in place using the set screws. For future use, you won't need to tighten both the fastening screws and set screws.

Step 5: Lever Closure

Achieve a firm assembly by closing the lever. Simply push the button as indicated in the provided picture to ensure a snug fit.



Step 6: Zeroing Preparation

Your riflescope is now ready for zeroing. Proceed with your zeroing process as needed.

Step 7: Uninstallation

When it's time to uninstall the mount, push the button again to release and remove it.

Please follow these steps carefully to ensure the proper installation and use of your PARD MT5 Quick-Release Mount.